

Nitrogen

WAG-089A-DD



2.2 : Non flammable, non toxic gas.

Warning



1 Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name : Nitrogen

SDS Nr : WAG-089A-DD

Chemical description : Nitrogen
CAS No :007727-37-9
EC No :231-783-9
Index No :---

Chemical formula : N2

Registration-No. : Listed in Annex IV / V REACH, exempted from registration.

Use : Industrial and professional. Perform risk assessment prior to use.

Company identification : Westfalen AG
Industrieweg 43
48155 MUENSTER Deutschland
Tel : 0049 2 51 6 95 0
Fax: 0049 2 51 6 95 1 94

E-Mail address (competent person): : sdb@westfalen-ag.de

Emergency telephone number : Tel. (+49)5459/80625

2 Hazards identification

Classification of the substance or mixture

Hazard Class and Category Code

Regulation EC 1272/2008 (CLP)

• Physical hazards : Gases under pressure - Compressed gas - Warning (H280)

Classification EC 67/548 or EC 1999/45 : Not included in Annex VI.

Not classified as dangerous preparation/substance.
No EC labelling required.

Label elements

Labelling Regulation EC 1272/2008 (CLP)

• Hazard pictograms



**Westfalen****SAFETY DATA SHEET**

Page : 2

Revised edition no : 0

Date : 14 / 9 / 2011

Supersedes : 0 / 0 / 0

Nitrogen**WAG-089A-DD****2 Hazards identification (continued)**

- Hazard pictograms code
- Signal word : Warning
- Hazard statements : H280 : Contains gas under pressure; may explode if heated.
- Precautionary statements
 - Storage : P403 : Store in a well-ventilated place.

Labelling EC 67/548 or EC 1999/45

Symbol(s) : None.

R Phrase(s) : None.

S Phrase(s) : None.

Other hazards

Other hazards : Asphyxiant in high concentrations.

3 Composition/information on ingredients

Substance / Preparation	: Substance.					
Substance name	Contents	CAS No	EC No	Index No	Registration no	Classification
Nitrogen	: 100 %	7727-37-9	231-783-9	----	NOTE 1	Press. Gas (H280)

Contains no other components or impurities which will influence the classification of the product.

Note 1: Listed in Annex IV / V REACH, exempted from registration.

Note 2: Registration deadline not expired.

Full text of R-phrases see chapter 16

4 First aid measures**First aid measures**

- **Inhalation** : In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

5 Fire-fighting measures

Specific hazards : Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products : None.

Extinguishing media

- **Suitable extinguishing media** : All known extinguishants can be used.

Specific methods : If possible, stop flow of product. Move away from the container and cool with water from a protected position.

Special protective equipment for fire fighters : In confined space use self-contained breathing apparatus.

6 Accidental release measures

Personal precautions : Evacuate area. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation.

Westfalen AG

Industrieweg 43 48155 MUNSTER Deutschland

Tel : 0049 2 51 6 95 0

Fax: 0049 2 51 6 95 1 94

In case of emergency : Tel. (+49)5459/80625

**Westfalen****SAFETY DATA SHEET**

Page : 3

Revised edition no : 0

Date : 14 / 9 / 2011

Supersedes : 0 / 0 / 0

Nitrogen**WAG-089A-DD****6 Accidental release measures (continued)****Environmental precautions** : Try to stop release.**Clean up methods** : Ventilate area.**7 Handling and storage****Handling** : Suck back of water into the container must be prevented.
Do not allow backfeed into the container.
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
Refer to supplier's container handling instructions.**Storage** : Keep container below 50°C in a well ventilated place.**8 Exposure controls/personal protection****Personal protection** : Ensure adequate ventilation.**9 Physical and chemical properties****Physical state at 20 °C** : Gas.
Colour : Colourless gas.
Odour : No odour warning properties.
Molecular weight [g/mol] : 28
Melting point [°C] : -210
Boiling point [°C] : -196
Critical temperature [°C] : -147
Vapour pressure [20°C] : Not applicable.
Relative density, gas (air = 1) : 0.97
Relative density, liquid (water=1) : Not applicable.
Solubility in water [mg/l] : 20**10 Stability and reactivity****Hazardous decomposition products** : None.**Chemical stability** : Stable under normal conditions.**11 Toxicological information****Toxicity information** : No known toxicological effects from this product.**12 Ecological information****Ecological effects information** : No known ecological damage caused by this product.**Water-endangerment class Germany** : WGK0 - In general not hazardous for aquatic environment.**13 Disposal considerations****General** : Do not discharge into any place where its accumulation could be dangerous.
To atmosphere in a well ventilated place.
Contact supplier if guidance is required.**Westfalen AG**

Industrieweg 43 48155 MUNSTER Deutschland

Tel : 0049 2 51 6 95 0

Fax: 0049 2 51 6 95 1 94

In case of emergency : Tel. (+49)5459/80625

**Westfalen****SAFETY DATA SHEET**

Page : 4

Revised edition no : 0

Date : 14 / 9 / 2011

Supersedes : 0 / 0 / 0

Nitrogen**WAG-089A-DD****14 Transport information****General information**

- UN number : 1950
- Labelling ADR, IMDG, IATA



: 2.2 : Non flammable, non toxic gas.

- Labelling ADR



: 2.2 : Non flammable, non toxic gas.

Land transport (ADR/RID)

- H.I. nr : --
- UN proper shipping name : UN1950 DRUCKGASPACKUNGEN, 2.2, 5A, (E)
- Transport hazard class(es) : 2
- Classification code : 5 A
- Packing group : A
- Packing Instruction(s) - General : P003 LP002
- Tunnel Restriction : E : Passage forbidden through tunnels of category E.

Sea transport (IMDG)

- Proper shipping name : AEROSOLS
- Class : 2.2
- IMO-IMDG code : Class 2
- IMO Packing group : P003
- IMDG-Marine pollution : YES ò
- Packing Instruction(s) : P003

Air transport (ICAO/IATA)

- Proper shipping name : AEROSOLS
- Class : 2
- IATA Packing group : A
- Passenger and Cargo Aircraft : Allowed.
- Packing Instruction(s) : Y203
203
- Packing Instruction(s) : 203

Other transport information

- : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
- Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
- Before transporting product containers:
 - Ensure that containers are firmly secured.
 - Ensure cylinder valve is closed and not leaking.
 - Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
 - Ensure valve protection device (where provided) is correctly fitted.

Westfalen AG

Industrieweg 43 48155 MUNSTER Deutschland

Tel : 0049 2 51 6 95 0

Fax: 0049 2 51 6 95 1 94

In case of emergency : Tel. (+49)5459/80625

**Westfalen****SAFETY DATA SHEET**

Page : 5

Revised edition no : 0

Date : 14 / 9 / 2011

Supersedes : 0 / 0 / 0

Nitrogen**WAG-089A-DD****14 Transport information (continued)**

- Ensure there is adequate ventilation.
- Compliance with applicable regulations.

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture : Ensure all national/local regulations are observed.

Seveso regulation 96/82/EC : Not covered.

16 Other information

Asphyxiant in high concentrations.

Keep container in a well-ventilated place.

Do not breathe the gas.

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws.

DISCLAIMER OF LIABILITY

: Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.
Details given in this document are believed to be correct at the time of going to press. Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

End of document**Westfalen AG**

Industrieweg 43 48155 MUENSTER Deutschland

Tel : 0049 2 51 6 95 0

Fax: 0049 2 51 6 95 1 94

In case of emergency : Tel. (+49)5459/80625