

Carbon dioxide

WAG-018A-DD



2.2 : Non flammable, non toxic gas.

Warning



1 Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name : Carbon dioxide
SDS Nr : WAG-018A-DD
Chemical description : Carbon dioxide
CAS No :000124-38-9
EC No :204-696-9
Index No :---
Chemical formula : CO2
Registration-No. : Listed in Annex IV / V REACH, exempted from registration.
Use : Industrial and professional. Perform risk assessment prior to use.
Company identification : Westfalen AG
Industrieweg 43
48155 MUENSTER Deutschland
Tel : 0049 2 51 6 95 0
Fax: 0049 2 51 6 95 1 94
E-Mail address (competent person): : sdb@westfalen-ag.de
Emergency telephone number : Tel. (+49)5459/80625

2 Hazards identification

Classification of the substance or mixture

Hazard Class and Category Code
Regulation EC 1272/2008 (CLP)

• Physical hazards : Gases under pressure - Compressed gas - Warning (H280)
Classification EC 67/548 or EC 1999/45 : Not included in Annex VI.
Not classified as dangerous preparation/substance.
No EC labelling required.

Label elements

Labelling Regulation EC 1272/2008 (CLP)

• Hazard pictograms



Carbon dioxide

WAG-018A-DD

2 Hazards identification (continued)

- Hazard pictograms code
- Signal word : Warning
- Hazard statements : H280 : Contains gas under pressure; may explode if heated.
- Precautionary statements
 - Storage : P403 : Store in a well-ventilated place.

Labelling EC 67/548 or EC 1999/45

Symbol(s) : None.

R Phrase(s) : None.

S Phrase(s) : None.

Other hazards

Other hazards : Asphyxiant in high concentrations.

3 Composition/information on ingredients

Substance / Preparation	: Substance.					
Substance name	Contents	CAS No	EC No	Index No	Registration no	Classification
Carbon dioxide	: 100 %	124-38-9	204-696-9	----	NOTE 1	Liq. Gas (H280)

Contains no other components or impurities which will influence the classification of the product.

Note 1: Listed in Annex IV / V REACH, exempted from registration.

Note 2: Registration deadline not expired.

Full text of R-phrases see chapter 16

4 First aid measures

First aid measures

- **Inhalation** : In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Low concentrations of CO₂ cause increased respiration and headache. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- **Skin/eye contact** : Immediately flush eyes thoroughly with water for at least 15 minutes. In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- **Ingestion** : Ingestion is not considered a potential route of exposure.

5 Fire-fighting measures

Specific hazards : Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products : None.

Extinguishing media

- **Suitable extinguishing media** : All known extinguishants can be used.

Specific methods : If possible, stop flow of product. Move away from the container and cool with water from a protected position.

Special protective equipment for fire fighters : In confined space use self-contained breathing apparatus.

**Westfalen****SAFETY DATA SHEET**

Page : 3

Revised edition no : 0

Date : 21 / 9 / 2011

Supersedes : 0 / 0 / 0

Carbon dioxide**WAG-018A-DD****6 Accidental release measures****Personal precautions**

: Evacuate area.
Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
Ensure adequate air ventilation.

Environmental precautions

: Try to stop release.
Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

Clean up methods

: Ventilate area.

7 Handling and storage**Handling**

: Suck back of water into the container must be prevented.
Do not allow backfeed into the container.
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
Refer to supplier's container handling instructions.

Storage

: Keep container below 50°C in a well ventilated place.

8 Exposure controls/personal protection**Personal protection**

: Ensure adequate ventilation.

Occupational Exposure Limits

: Carbon dioxide : ILV (EU) - 8 H - [mg/m³] : 9000
Carbon dioxide : ILV (EU) - 8 H - [ppm] : 5000
Carbon dioxide : TLV© -TWA [ppm] : 5000
Carbon dioxide : TLV© -TWA [ppm] : 5000
Carbon dioxide : TLV© -TWA [ppm] : 5000
Carbon dioxide : TLV© -STEL [ppm] : 30000
Carbon dioxide : TLV© -STEL [ppm] : 30000
Carbon dioxide : TLV© -STEL [ppm] : 30000
Carbon dioxide : TLV© -STEL [ppm] : 30000

9 Physical and chemical properties**Physical state at 20 °C**

: Gas.

Colour

: Colourless.

Odour

: No odour warning properties.

Molecular weight [g/mol]

: 44

Melting point [°C]

: -56.6

Boiling point [°C]

: -78.5 (s)

Critical temperature [°C]

: 30

Vapour pressure [20°C]

: 57.3 bar

Relative density, gas (air = 1)

: 1.52

Relative density, liquid (water=1)

: 0.82

Solubility in water [mg/l]

: 2000

Flammability range [vol% in air]

: Non flammable.

Other data

: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

Carbon dioxide

WAG-018A-DD

10 Stability and reactivity

Hazardous decomposition products : None.

Chemical stability : Stable under normal conditions.

11 Toxicological information

Toxicity information : In high concentrations cause rapid circulatory insufficiency. Symptoms are headache, nausea and vomiting, which may lead to unconsciousness.

12 Ecological information

Ecological effects information : When discharged in large quantities may contribute to the greenhouse effect.

Global warming potential [CO2=1] : 1

Water-endangerment class Germany : WGK0 - In general not hazardous for aquatic environment.

13 Disposal considerations

General : Do not discharge into any place where its accumulation could be dangerous.
To atmosphere in a well ventilated place.
Discharge to atmosphere in large quantities should be avoided.
Contact supplier if guidance is required.

14 Transport information

General information

- **UN number** : 1950

- **Labelling ADR, IMDG, IATA**



: 2.2 : Non flammable, non toxic gas.

- **Labelling ADR**



: 2.2 : Non flammable, non toxic gas.

Land transport (ADR/RID)

- **H.I. nr**

: --

- **UN proper shipping name**

: UN1950 DRUCKGASPACKUNGEN, 2.2, 5A, (E)

- **Transport hazard class(es)**

: 2

- **Classification code**

: 5 A

- **Packing group**

: A

- **Packing Instruction(s) - General**

: P003 LP002

- **Tunnel Restriction**

: E : Passage forbidden through tunnels of category E.

Sea transport (IMDG)

- **Proper shipping name** : AEROSOLS

**Westfalen****SAFETY DATA SHEET**

Page : 5

Revised edition no : 0

Date : 21 / 9 / 2011

Supersedes : 0 / 0 / 0

Carbon dioxide**WAG-018A-DD****14 Transport information (continued)**

- Class	: 2.2
- IMO-IMDG code	: Class 2
- IMO Packing group	: P003
- IMDG-Marine pollution	: YES ò
- Packing Instruction(s)	: P003

Air transport (ICAO/IATA)

- Proper shipping name	: AEROSOLS
- Class	: 2
- IATA Packing group	: A
- Passenger and Cargo Aircraft	: Allowed.
- Packing Instruction(s)	: Y203 203
- Packing Instruction(s)	: 203

Other transport information

: Avoid transport on vehicles where the load space is not separated from the driver's compartment.
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
Before transporting product containers:
- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.
- Ensure there is adequate ventilation.
- Compliance with applicable regulations.

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture	: Ensure all national/local regulations are observed.
Seveso regulation 96/82/EC	: Not covered.

16 Other information

Asphyxiant in high concentrations.

Keep container in a well-ventilated place.

Do not breathe the gas.

Contact with liquid may cause cold burns/frostbite.

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws.

DISCLAIMER OF LIABILITY

: Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.
Details given in this document are believed to be correct at the time of going to press. Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

End of document**Westfalen AG**

Industrieweg 43 48155 MUENSTER Deutschland

Tel : 0049 2 51 6 95 0

Fax: 0049 2 51 6 95 1 94

In case of emergency : Tel. (+49)5459/80625